



TECHNICAL DATA

TK946578 3.5 mil permanent removable double coated white vinyl

Colors:	White		
Description:	3.5 mil double coated flexible white opaque vinyl coated with a removable pressure-sensitive acrylic adhesive on one side and a permanent pressure-sensitive acrylic adhesive on the other side with a single 80 lb double-faced liner. Ideal for promotional graphics, product ID labels, nameplates, POS displays and event and trade show displays/graphics		
Features & Benefits:	<ul style="list-style-type: none"> • Proven product performance at a lower cost • Provides an excellent opaque barrier with superior wet-out characteristics • Removable acrylic adhesive adheres to a variety of surfaces and removes cleanly from most surfaces • High peel, permanent acrylic adhesive resists cold flow and ooze • Single 80 lb liner is moisture-stable 		
Construction:	80 lb double-faced liner 0.8-0.9 mil removable adhesive 3.5 mil white opaque vinyl 0.8-0.9 mil permanent adhesive		
Minimum Application Temperature:	+ 50°F (10°C)		
Service Temperature Range:	-20° F to 176° F -29° C to 80° C		
Adhesion:		Oz/in (N/m)	ASTM D 903
	Stainless Steel		
	Removable	18 (198)	
	Permanent	56 (616)	
	Acrylic		
	Removable	57 (627)	
	Permanent	62 (682)	
	Glass		
	Removable	2 (22)	
	Permanent	57 (627)	
Expected Shear: (hours)	Removable 40 hours		ASTM D 3643 Method A
	Permanent 5 hours		
Tack: (gm)	Removable: 160		ASTM D 2979
	Permanent: 410		
Exterior Durability:	Depends on the substrate, both adhesives are suitable for outdoor use		
Storage Stability:	2 years at 70°F (21°C) and 50% RH		