



TECHNICAL DATA

TK978378 .5 mil removable/permanent clear PET

Colors:	Clear		
Description:	0.5 mil double coated clear polyester with a clear removable pressure-sensitive acrylic adhesive on one side and an optically-clear permanent pressure-sensitive adhesive on the other side with a single 80 lb liner. Ideal for promotional graphics, product ID labels, nameplates, point-of-sale displays and event & trade show displays/graphics		
Features & Benefits:	<ul style="list-style-type: none"> • Low tack removable adhesive removes easily and cleanly from a variety of surfaces • High shear, optically-clear, permanent adhesive has excellent heat, UV and humidity resistance, and bonds well to a wide variety of surfaces • Single 80lb liner double-faced liner is moisture-stable 		
Construction:	1 mil removable adhesive .5 mil clear PET 1 mil permanent adhesive 80 lb liner		
Minimum Application Temperature:	+ 50°F (10°C)		
Service Temperature Range:	-20° F to 302° F -29° C to 150° C		
Adhesion:		Oz/in (N/m)	ASTM D 903
	Stainless Steel		
	Removable	12 (132)	
	Permanent	19 (209)	
	Acrylic		
	Removable	13 (143)	
	Permanent	29 (319)	
	Glass		
	Removable	12 (132)	
	Permanent	26 (286)	
Expected Shear: (hours)	Removable 1 hour minimum		ASTM D 3643 Method A
	Permanent 100 + hours		
Tack: (gm)	Removable: 360		ASTM D 2979
	Permanent: 400		
Exterior Durability:	Depends on the substrate, both adhesives are suitable for outdoor use		
Storage Stability:	2 years at 70°F (21°C) and 50% RH		