



I89160M

PRODUCT DATA

DigiGo™ 60# Matte Litho Paper with Permanent Adhesive and 80# Scored Back Liner

Facestock Description: 60# Matte Litho Optimized For Digital Printing

Dull coated finish with a superior smudgeproof surface and a reduced non-glare gloss level. Optimized for use with HP Indigo, Xerox Igen3, and Kodak Nexpress printers. Typical end uses include point of purchase displays, package and carton labels, and mailing labels.

Basis Weight (25 x38 / 500)	60
Caliper, mils	3.6
Tensile, lbs./in., MD / CD	36 / 14
Tear, g, MD / CD	46 / 53
Brightness, %	87
Opacity, %	94.5
Gloss, %	25
pH	7-8
Regulatory Compliances	FDA 21 CFR 175.105 for incidental food contact, CONEG, ASTM F963a Child Toy Safety, California Prop. 65, and NAFTA.

Adhesive Description: Permanent

An emulsion acrylic adhesive with good initial tack and good adhesion to a wide variety of surfaces. Trims and die-cuts cleanly.

Type	Cold Temperature Permanent
Classification	Emulsion Acrylic
Regulatory Compliances	FDA 21 CFR 175.105 for incidental food contact, CONEG, Heavy Metals, ASTM F963A Child Toy Safety, Acute Oral Toxicity, Primary Dermal Irritant, Primary Eye Irritant, and NAFTA
pH	Alkaline
Minimum Application Temp.	+35°F
Service Temperature Range	-10°F to +200°F

Liner Description: 80# Scored Back

Clay-coated kraft liner with vertical scores ever 1 1/4". Bending the sheet at the score will cause the score to break apart and the liner can then be easily removed in multiple pieces.

Basis Weight (25 x 38 / 500)	80 +/- 10%
Caliper, mils	4.2
Brightness, %	78
Opacity, %	91
Tensile, lbs./in. MD / CD	49 / 26
Tear, G, MD / CD	69 / 73
Gloss, 75°	58.0
Regulatory Compliances	FDA for incidental food contact, CONEG, Heavy Metals, California Clean Water (Proposition 65), free of natural rubber latex, and Elemental Chlorine Free (ECF).

All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any product for their particular application. The above specifications are based on typical values and most current information.

Shelf Lie: One year when stored at 72°F / 50% RH.

Any order for these products will be subject to Tekra Corporation's terms and conditions of sale.