



Wide Format UV Inkjet Media

Product Data

JetView Clear Polyester for UV Inkjet

Product Description

JetView Clear Polyester is for UV Inkjet printers. The film is a dimensionally stable, image enhancing clear film that can be printed on the front, back, or both sides.

Typical Applications

Reverse printed light boxes, window displays, illuminated signs, point-of-purchase signs.

Available Gauges (stocked & custom):

500, 700, and 1000 gauge

Polyester Data:

| Property | Value | Units | Test |
|------------------------|--------|-------|----------------------------|
| Optical | | | |
| Haze | 0.4 | % | ASTM D1003 |
| TLT | 88 | % | ASTM D1003 |
| Physical | | | |
| C.O.F. (dynamic) A-B | 0.5 | | ASTM D1894 |
| Elongation at Break MD | 200 | % | ASTM D882A |
| Elongation at Break TD | 120 | % | ASTM D882A |
| Tensile Strength MD | 24,000 | psi | ASTM D882A |
| Tensile Strength TD | 30,000 | psi | ASTM D882A |
| Yield Strength MD | 14,000 | psi | ASTM D882A |
| Yield Strength TD | 14,000 | psi | ASTM D882A |
| Thermal | | | |
| Shrinkage MD (190°C) | 1.7 | % | Unrestrained @ 190°C/5 min |
| Shrinkage TD (190°C) | 1.9 | % | Unrestrained @ 190°C/5 min |

The applications suggestions, specifications and other data described here are based on experience that is believed by Tekra Corporation and Hanita Coatings to be reliable. Because of the characteristics of these products, you should, before using these products in production, perform your own tests to determine to your satisfaction whether these products are acceptable and suitable for your particular purposes under your operation conditions.

Any order for these products will be subject to Seller's terms and conditions of sale.