



Wide Format UV Inkjet Media

Product Data

JetView Diffused Polyester for UV Inkjet

Product Description

JetView Diffused Polyester is for UV Inkjet printers. It is a bright diffused film designed to be front printed making unmatched light box images.

Typical Applications

Light-boxes, illuminated signs, point-of-purchase signs

Available Gauges (stocked & custom):

760 gauge

Polyester Data:

Physical

| Property | Thickness | Value | Units | Test |
|------------------------|-----------|-------------|---------------------|------------|
| C.O.F. (static) | 760 | 0.3 | | ASTM D1894 |
| Density | 760 | 1.4 | g/cc | ASTM D1505 |
| Elongation at Break MD | 760 | 150 | % | ASTM D882A |
| Elongation at Break TD | 760 | 130 | % | ASTM D882A |
| Tensile Strength MD | 760 | 29.9 | kpsi | ASTM D882A |
| Tensile Strength TD | 760 | 31.1 | kpsi | ASTM D882A |
| Yield (nominal) | 760 | 2,600 | ln ² /lb | ASTM D882A |
| Optical Density | 760 | 4.5 minimum | | ASTM D882A |

The applications suggestions, specifications and other data described here are based on experience that is believed by Tekra Corporation and Hanita Coatings to be reliable. Because of the characteristics of these products, you should, before using these products in production, perform your own tests to determine to your satisfaction whether these products are acceptable and suitable for your particular purposes under your operation conditions.

Any order for these products will be subject to Seller's terms and conditions of sale.