



Wide Format UV Inkjet Media

Product Data

JetView White Light Block Polyester for UV Inkjet

Product Description

JetView White Light Block Polyester is for UV Inkjet printers. It is a totally opaque film. JetView White Light Block is the film of choice where light and shadow from behind could weaken the front printed image.

Typical Applications

Banner Stands, pop up displays, signage, poster stands, and window displays

Available Gauges (stocked & custom):

800 gauge

Polyester Data:

Property	Thickness	Value	Units	Test
General				
Relative Density (at 23°C)	800	1.51	g/cm ³	ASTM D1505-85
Area Yield	800	3.31	m ² /kg	ASTM D1505-85
Mechanical				
Elongation at Break	800	120	%	ASTM D882-83
Yield Strength	800	9.8	kgf/mm ²	ASTM D882-83
Tensile Strength at break MD	800	19.3	kgf/mm ²	ASTM D882-83
Tensile Strength at break TD	800	26.0	kgf/mm ²	ASTM D882-83
Optical				
Whiteness	800	92		ASTM E 313-79
				ASTM D1003-77 (Gardner Hazemeter)
Optical Density	800	4.5 minimum		
Thermal				
Upper Melt Temperature	800	255 - 260	°C	ASTM E794-85
Shrinkage MD	800	2.5	%	5 min at 190°C
Shrinkage TD	800	0.75	%	5 min at 190°C

The applications suggestions, specifications and other data described here are based on experience that is believed by Tekra Corporation and Hanita Coatings to be reliable. Because of the characteristics of these products, you should, before using these products in production, perform your own tests to determine to your satisfaction whether these products are acceptable and suitable for your particular purposes under your operation conditions.

Any order for these products will be subject to Seller's terms and conditions of sale.