



TECHNICAL DATA

4 mil Flexible Vinyls with Removable Adhesive

Colors:	Clear or White
Description:	Flexible Vinyls coated with removable acrylic adhesive designed to produce high quality but economical markings, labels, emblems and signs. Screen printing is recommended.
Construction:	3.4 - 4 mil flexible polyvinyl chloride .5 - .7 mil removable acrylic adhesive 7.0 mil 90# liner polyethylene coated 2-sides
Removability:	6-12 months from a wide variety of plastic/glass substrates. It is not intended for application to paper.
Minimum Application Temperature:	+ 55° F
Application Surface:	Flat
Service Temperature Range:	-40° F to 176° F for White -35° F to 150° F for Clear
Adhesion:	32oz/in 15 minute applied White 35 oz/in 24 hour applied White 34 oz/in 15 minute applied Clear 48 oz/in 24 hour applied Clear
Water Resistance:	Excellent
Solvent Resistance:	When properly applied and edge sealed, good resistance to most petroleum solvents and aliphatic solvents. Will degrade upon prolonged exposure to petroleums.
Chemical Resistance:	Resistant to mild acids, alkalines & salt.
Dimensional Stability:	Fair
Storage Stability:	1 year at 73° F and 50% RH
Outdoor Durability:	Clear 6 months and White 12 months when properly applied and edge sealed.