



Hanita Coatings



HP INDIGO® OPTIMIZED SUBSTRATES

I34108

Product Data

## 8mil (200 micron) White Static Cling with 90# Liner

Dura-Go substrates are HP Indigo-licensed and were jointly developed by Hanita Coatings, Tekra Corporation and HP Indigo to create the premier product line of film substrates for the HP Indigo presses.

Our proprietary primer coatings provide a number of benefits, including:

Reliable, superior ink adhesion

High definition of colors

Long shelf life, guaranteed to print for 6 months after purchase on Static Cling when stored at less than 72F and less than 50% relative humidity

With static cling, it is the nature of the plasticizer in this film to continually migrate to the surface. This may create hazy surface appearance and drop in surface energy. The surface of the cling vinyl may have liner impressions, flow lines and blotches

Recommendations for product use:

- Wet method is recommended for large decal
- Use rubber roll to smooth out decals, squeegee is not recommended

Product Data	Value	Test Method
Thickness (mils)	Film: 7.1 +/- 10%	ASTM D 3652
	Liner: 6.7 +/- 10%	
Expected Exterior Life	Indoor Use Only	
Minimum Application Temperature	50°F (10°C)	
Service Temperature Range	-10°F to 176°F (-23.3°C to 80°C)	

The application suggestions, specifications and other data described here are based on experience that is believed by Tekra and Hanita Coatings to be reliable. Because of the characteristics of these products, you should, before using these products in production, perform your own tests to determine to your satisfaction whether these products are acceptable and suitable for your particular purposes under your operation conditions. Any order for these products will be subject to Seller's terms and conditions of sale.