



HP INDIGO® OPTIMIZED SUBSTRATES

I34108

## Product Data

### 8mil (200 micron) White Static Cling Vinyl with 8 pt. Board

Dura-Go substrates are HP certified by RIT to create the premier product line of film for the HP Indigo presses.

Our coating provides a number of benefits, including:

- Reliable, superior ink adhesion

- High definition of colors

- Long shelf life, guaranteed to print for 6 months after purchase on Static Cling when stored at less than 72F and less than 50% relative humidity

With static cling, it is the nature of the plasticizer in this film to continually migrate to the surface. This may create hazy surface appearance and drop in surface energy. The surface of the cling vinyl may have liner impressions, flow lines and blotches

Recommendations for product use:

- Wet method is recommended for large decal
- Use rubber roll to smooth out decals, squeegee is not recommended

Product Data	
Thickness	8.0 mil
Liner	8 pt. Kromekote Board
Interior Durability	2 years mid-continental U.S. vertical
Minimum Surface/Ambient Air	
Application Temperature	+35° F
Service Temperature Range	10° F (-17° C) to +160° F (60° C)
Water Resistance	Excellent
Humidity Resistance	Excellent
Adhesion	Excellent: Both sides will adhere securely to glass and other highly polished smooth surfaces
Shelf Life	6 months when stored at 75% and 50% relative humidity
Available Size	12" x 18" sheets and 13" x 19" sheets

The application suggestions, specifications and other data described here are based on experience that is believed by Tekra to be reliable. Because of the characteristics of these products, you should, before using these products in production, perform your own tests to determine to your satisfaction whether these products are acceptable and suitable for your particular purposes under your operation conditions. Any order for these products will be subject to Seller's terms and conditions of sale.