



I89160G

PRODUCT DATA

DigiGo™ 60# Gloss Paper with Permanent Adhesive and 80# Scored Back Liner

Facestock Description: 60# Gloss Optimized For Digital Printing

High gloss, mirror-like finish with excellent ink receptivity. High quality color reproduction. Optimized to be run on the HP Indigo, Xerox Igen3, and Kodak Nexpress digital presses. Typical end uses include high quality label applications, consumer packaging, appliance labeling, and decorative labels.

Basis Weight (25 x38 / 500)	60
Caliper, mils	4.0
Tensile, lbs./in., MD / CD	26 / 16
Tear, g, MD / CD	49 / 51
Brightness, %	90
Opacity, %	90
Gloss, %	82
pH	Alkaline
Regulatory Compliances	FDA 21 CFR 175.105 for incidental food contact, CONEG, ASTM F963-96A Child Toy Safety, Prop. 65, and NAFTA. Free of natural latex.

Adhesive Description: Permanent

An emulsion acrylic adhesive with good initial tack and good adhesion to a wide variety of surfaces. Trims and die-cuts cleanly.

Type	Cold Temperature Permanent
Classification	Emulsion Acrylic
Regulatory Compliances	FDA 21 CFR 175.105 for incidental food contact, CONEG, Heavy Metals, ASTM F963A Child Toy Safety, Acute Oral Toxicity, Primary Dermal Irritant, Primary Eye Irritant, and NAFTA
pH	Alkaline
Minimum Application Temp.	+35°F
Service Temperature Range	-10°F to +200°F

Liner Description: 80# Scored Back

Clay-coated kraft liner with vertical scores every 1 1/4". Bending the sheet at the score will cause the score to break apart and the liner can then be easily removed in multiple pieces.

Basis Weight (25 x 38 / 500)	80 +/- 10%
Caliper, mils	4.2
Brightness, %	78
Opacity, %	91
Tensile, lbs./in. MD / CD	49 / 26
Tear, G, MD / CD	69 / 73
Gloss, 75°	60.0
Regulatory Compliances	FDA for incidental food contact, CONEG, Heavy Metals, California Clean Water (Proposition 65), free of natural rubber latex, and Elemental Chlorine Free (ECF).

All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any product for their particular application. The above specifications are based on typical values and most current information.

Shelf Life: One year when stored at 72°F / 50% RH.

Any order for these products will be subject to Tekra's terms and conditions of sale.