



### 189160SG

## **PRODUCT DATA**

# DigiGo<sup>™</sup> 60# Semi Gloss Paper with Permanent Adhesive and 80# Scored Back Liner

#### Facestock Description: 60# Semi Gloss Optimized For Use On Digital Presses

Bright blue-white shade with a medium gloss level and good opacity. Has a smooth finish and uniform surface. Is top coated and optimized for use on the HP Indigo, Xerox Igen3, and Kodak Nexpress digital presses. Contains 10% post consumer fiber.

Basis Weight (25 x38 / 500)	60
Caliper, mils	2.8
Brightness, %	90
Opacity, %	92
Gloss, 60°	72
Regulatory Compliances	CONEG, Heavy Metals, ASTM for Toy Safety, and
	NAFTA

#### **Adhesive Description: Permanent**

An emulsion acrylic adhesive with good initial tack and good adhesion to a wide variety of surfaces. Trims and die-cuts cleanly.

Туре	Cold Temperature Permanent
Classification	Emulsion Acrylic
Regulatory Compliances	FDA 21 CFR 175.105 for incidental food contact,
	CONEG, Heavy Metals, ASTM F963A Child Toy
	Safety, Acute Oral Toxicity, Primary Dermal Irritant,
	Primary Eye Irritant, and NAFTA
рН	Alkaline
Minimum Application Temp.	+35°F
Service Temperature Range	-10°F to +200°F

#### Liner Description: 80# Scored Back

Clay-coated kraft liner with vertical scores ever 1 1/4". Bending the sheet at the score will cause the score to break apart and the liner can then be easily removed in multiple pieces.

Basis Weight (25 x 38 / 500)	80 +/- 10%
Caliper, mils	4.2
Brightness, %	78
Opacity, %	91
Tensile, lbs./in. MD / CD	49 / 26
Tear, G, MD / CD	69 / 73
Gloss, 75°	60.0
Regulatory Compliances	FDA for incidental food contact, CONEG, Heavy
	Metals, California Clean Water (Proposition 65), free
	of natural rubber latex, and Elemental Chlorine Free
	(ECF).

All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any product for their particular application. The above specifications are based on typical values and most current information. Shelf Lie: One year when stored at 72°F / 50% RH.

Any order for these products will be subject to Tekra Corporation's terms and conditions of sale.