



I8P160UC

PRODUCT DATA

DigiGo™ 60# Uncoated Offset Paper with Permanent Adhesive and 80# Scored Back Liner

Facestock Description: 60# Uncoated Offset Paper Optimized for Digital Printing

Engineered to run on HP Indigo, Xerox Igen3 and Kodak Nexpress digital printing platforms. Bright white uncoated offset (96 brightness). Is economically priced, high strength, and absorbent surface. Suitable for offset, flexographic, and dot matrix printing applications.

Basis Weight (25 x38 / 500)	60
Caliper, mils	4.7
Tensile, lbs./in., MD / CD	32.5 / 16.0
Tear, g, MD / CD	64.2 / 70.4.
Brightness, %	96
Opacity, %	94
Smoothness, Sheffield	101
Regulatory Compliances	ASTM F963-69a Child Toy Safety, the California Clear Water and Clear Air Act (Prop. 65), CONEG, and NAFTA. Lignin free and free of natural latex.

Adhesive Description: Permanent

An emulsion acrylic adhesive with good initial tack and good adhesion to a wide variety of surfaces. Trims and die-cuts cleanly.

Type	Cold Temperature Permanent
Classification	Emulsion Acrylic
Regulatory Compliances	FDA 21 CFR 175.105 for incidental food contact, CONEG, Heavy Metals, ASTM F963A Child Toy Safety, Acute Oral Toxicity, Primary Dermal Irritant, Primary Eye Irritant, and NAFTA
pH	Alkaline
Minimum Application Temp.	+35°F
Service Temperature Range	-10°F to +200°F

All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any product for their particular application. The above specifications are based on typical values and most current information.
Shelf Lie: One year when stored at 72°F / 50% RH.

Any order for these products will be subject to Tekra Corporation's terms and conditions of sale.