



TKX82204R

Product Data

4 mil White Vinyl with Removable Adhesive 90# Liner

General Description: This is a topcoated white matte flexible vinyl film with a removable pressure sensitive acrylic adhesive and backed with a two-sided poly coated lay flat release liner design for use with toner based printers.

TYPICAL CHARACTERISTICS

Target Adhesion Values (PSTC-1, 180° peel @ 12"/min., 73°F, on Stainless Steel)	15 min.	24 hr.
Minimum Application Temperature	3 oz./inch	2 oz./inch
Service Temperature Range	50°F	
Shelf Life (at 73°F, 50% RH)	-40°F to +180°F	
	2 years	

CHEMICAL RESISTANCE

Distilled Water (24 hr)	Slight Effect
Detergent (24 hr)	No Effect
10% HCl (10 min)	NA
10% Ammonium Hydroxide (10 min)	Slight Effect
Anti-Freeze (24 hr)	No Effect
SAE 20 Motor Oil (24 hr)	No Effect
Gasoline (1 hr)	Noticeable Lifting

Applications

- Point of purchase graphics
- Promotional displays
- Multiple color labels and decals

Note: This product removes easily from most surfaces. However, application environment and certain surfaces such as vinyl (PVC), varnished wood, acrylic polycarbonate may cause increased adhesion and adhesive transfer. We recommend that all surfaces be tested for compatibility and removability.

The applications suggestions, specifications and other data described here are based on experience that is believed by Tekra Corporation to be reliable. Because of the characteristics of these products, you should, before using these products in production, perform your own tests to determine to your satisfaction whether these products are acceptable and suitable for your particular purposes under your operation conditions.

Any order for these products will be subject to Seller's terms and conditions of sale.