





V3F005
Product Data

5mil White Matte Yupo®

Applications: - Wide format posters

- Backlit media for scrollers or light boxes

Benefits: - Excellent print resolution and anchorage

- Lighter weight and more durable than other media

For use with pigment ink for high resistance to weathering

Printable By: - Solvent and Ecosolvent wide format printers such as but not limited to:

- Mimaki JV3 SP

- Roland Soljet

- Seiko 64S

- Scitex Vision Grandjet

- Scitex Vision Pressjet

- Scitex Vision Idanit

- Plus other ecosolvent printers

Product Specifications:

Item Number	Apperance			Tensile Strength		Elongation at Break		Heat Resistance
		Thicknes	Yield	MD	TD	MD	TD	Polyolefinic based film
V3F005	White Matte	5 mil	10	11	30	120	25	should not be used at
Units		μm	m²/Kg	Kgf/mm ²		%		temperatures over 80° C
Test Methods				ASTM D 882-83		ASTM D 882-83		

In the event of any post-print processing applications, a minimum of 24 hours is recommended between printing and any additional processes. This is especially important for any processes that will come in direct contact with the ink, such as adhesive lamination. For best results, consult your ink manufacturer's recommendation of ink post-cure time, as inks may vary.

The applications suggestions, specifications and other data described here are based on experience that is believed by Tekra and Hanita Coatings to be reliable. Because of the characteristics of these products, you should, before using these products in production, perform your own tests to determine to your satisfaction whether these products are acceptable and suitable for your particular purposes under your operation conditions.