





V8B205

Product Data

5mil Translucent Both Side Visible Matte Polyester with a Clear Removable Adhesive

Applications: - Point of Purchase Window Signs

- Window Graphics

Benefits: - Excellent print resolution and anchorage

- Robust handling properties

- Image can be viewed from both sides

- For use with pigmented ink for high resistance to weathering

Printable By: - Solvent and Ecosolvent wide format printers such as but not limited to*:

- NUR Tempo Q

- Mimaki JV3

- Roland Soljet

- HP Scitex Turbojet

- Durst Rho 160

* Print compatibility subject to test

Product Specifications:

Item Number	Apperance	I I		Tensile Strength		Elongation at Break		Heat Resistance	
		Thicknes	Yield	MD	TD	MD	TD	MD	TD
V8B105	Matte	5 mil	4.3	21	24	150	100	1.3	0.5
Units		μm	m²/Kg	Kgf/mm ²		%			
Test Methods				ASTM D 882-83		ASTM D 882-83		30 min at 130° C	

In the event of any post-print processing applications, a minimum of 24 hours is recommended between printing and any additional processes. This is especially important for any processes that will come in direct contact with the ink, such as adhesive lamination. For best results, consult your ink manufacturer's recommendation of ink post-cure time, as inks may vary.

The applications suggestions, specifications and other data described here are based on experience that is believed by Tekra and Hanita Coatings to be reliable. Because of the characteristics of these products, you should, before using these products in production, perform your own tests to determine to your satisfaction whether these products are acceptable and suitable for your particular purposes under your operation conditions.

Any order for these products will be subject to Seller's terms and conditions of sale