



# TECHNICAL DATA

## 1 mil Clear Top Coated Permanent Polyester with 90# liner

Colors:	Clear		
Description:	A print receptive clear polyester film coated with a permanent pressure sensitive acrylic adhesive and with two side poly coated lay flat kraft release liner.		
Construction:	Film: 1.0 mil	+/- 10%	
	Adhesive: 1.0 - 1.1 mil	+/- 0.1	
	Liner: 6.9 mil	+/- 10%	
Dimensional Stability (%):	No shrinkage observed	On Al panel at 160°F for 24 hr.	
Adhesion Properties:	Stainless Steel	48 oz/in	528 N/m
	Acrylic	61 oz/in	671 N/m
	Glass	43 oz/in	473 N/m
	Polypropylene	27 oz/in	297 N/m
Expected Shear (hours):	25	ASTM D 3654 Method A (1 hour dwell, 1 sq. in. 4 lb load)	
Tack (gm):	830	ASTM D 2979	
Shelf Life:	2 years from date of manufacture of product when properly stored at 70°F (21°C) and 50% relative humidity		
Min. Application Temperature:	50°F (10°C)		
Expected Exterior Life:	2 years		
Service Temp. Range:	-40°F to 302°F (-40°C to 150°C)		