



TECHNICAL DATA

3.5 mil Economy Clear Flexible Vinyl NTC with Permanent Adhesive

| | | | |
|---------------------------------|--|----------------------|---------------------|
| Colors: | Clear | | |
| Description: | High gloss flexible vinyl is ideal for promotional multiple color labels and decals, p.o.p. graphics and other identification pieces. Ideal for screen printing. | | |
| Construction: | 3.5 mil flexible, gloss clear non-topcoated vinyl 0.8 mil permanent acrylic adhesive 6.7 mil 90# polycoated kraft liner | | |
| Service Temperature Range: | -40°F to +180°F | | |
| Minimum Application Temperature | 50°F | | |
| Adhesion: | 180° peel @ 12"/min. 73°F, on stainless steel (PSTC-1) | | |
| Average Adhesion Values: | Stainless Steel | 15 min. 3.2lbs/in | 24 hr. 5.1lbs/in |
| Shelf Life: | 2 years from date of manufacture of product when properly stored at 73° F and 50% relative humidity | | |
| Outdoor Durability: | 1-2 years | | |
| Chemical Resistance: | Distilled Water (24 hr) | No Effect | |
| | Detergent (24 hr) | No Effect | |
| | 10% HCl (10 min) | No Effect | |
| | 10% Ammonium Hydroxide (10 min) | No Effect | |
| | Anti-Freeze (24 hr) | No Effect | |
| | SAE 20 Motor Oil (24 hr) | No Effect | |
| | Gasoline (1 hr) | No Effect | |
| Printing Methods: | Screen (conventional), UV Screen, UV Offset, Hot Stamp, Thermal Transfer | | |