



TECHNICAL DATA

P20W

GENERAL DESCRIPTION:

This is a topcoated white polyester film coated with a permanent pressure sensitive acrylic adhesive and backed with a two-side polycoated lay flat release liner.

PRODUCT DATA	VALUE	TEST METHOD
PHYSICAL PROPERTIES		
Thickness (mil)	Film: 2.0 (51) +/- 10% Adhesive: 1.0-1.1 (25-28) +/- .1 (3) Liner: 6.9 (175) +/- 10%	ASTM D 3652
Dimensional stability	No shrinkage observed	On A1 panel at 160° (71° C) for 24 hr.
ADHESION PROPERTIES **		
Adhesion from	Average oz/in (N/m)	
Stainless Steel	60 (660)	ASTM D 903
Acrylic	71 (781)	
Glass	54 (594)	
Expected Sheer (hours)	75	ASTM D 3654 Method A (1 hr dwell)
Tack (gm)	550	ASTM D 2979

** For guidance only, not to be used for setting specifications. Due to the custom nature of this product, the data presented are based on three or less production runs.

EXPECTED EXTERIOR LIFE	Two Years
SERVICE TEMPERATURE RANGE	-40° F to 302° F (-40° C TO 150° C)
MINIMUM APPLICATION TEMPERATURE	50 F (10 C)
STORAGE STABILITY	Two Years stored at 70° F (21° C) and 50% rh

UL Approval: (File #: MH16183)