

DPF 210 Polyester Roll-Up Banner

Digital Print Banner

DPF 210 is a 9.8-mil (250 micron) premium, semi-rigid, coated polyester banner that is used in “roll-up” or “pop-up” banner applications. It has a gray, block-out layer that provides excellent opacity. DPF 210 is available in satin finish and yields high print resolution and image quality. It also has excellent lay-flat properties with minimal edge-curl. DPF 210 is compatible with eco-solvent and solvent inks. Please use proper handling and correct profiles with appropriate heater settings for optimal prints.

APPLICATIONS & FEATURES

- Digital printing with a wide variety of direct print systems.
- Indoor “roll-up and pop-up” display systems.
- Exhibitions, advertisements and point-of-purchase displays.

PERFORMANCE & PHYSICAL DATA

PROPERTY	TYPICAL VALUE
WEIGHT (GRAMS/SQ M)	340 ± 20gr (10 oz ± 0.03 oz)
THICKNESS (MIL)	9.8-mil (250 micron)
COLOR	Max DE 1.0 from color standard
OPACITY/CONTRAST RATIO	95% + 5%
GLOSS (GLOSS METER 60° REFLECTION)	0-15%
TENSILE STRENGTH (WARP, WEFT)	Min. 50 lbs/in, 100 lbs/in
ELONGATION (WARP, WEFT)	Min. 100%, 25%
TEAR STRENGTH	Min. 15 lbs/in
PRINTING	Printable with Eco-Solvent and Solvent inks
SHELF LIFE	1 year from production date
DURABILITY	Indoor, 1 year

*Standard Terms & Conditions Apply

Effective Date 02.13

USA: 2811 S. Harbor Blvd. Santa Ana, CA 92704 – Telephone: 800-854-0361 – Fax: 714-540-7190

Customer Service: Telephone: 800-232-7161 – Fax: 800-329-2756 – Technical Services: 877-275-6698

EUROPE: North Sea Building, Gevers Deynootweg 93, 4th Floor, 2586BK Den Haag, The Netherlands – Telephone: +31 (0) 70 354-4311 – Fax: +31 (0) 70 355-7721

INDIA: 4F1 Court Chambers, 35 - New Marines Lines, Mumbai 400 020 – Telephone: +91 99 6755-3895

www.arlon.com

TERMS & CONDITIONS

The following is made in lieu of all warranties expressed or implied:

All statements, technical information and recommendations published by Arlon relating to Arlon products are based on tests believed to be reliable and within the accuracy of the equipment used to obtain the specific values. Their accuracy or completeness is not guaranteed and Arlon makes no warranty with regard thereto. Seller's and manufacturer's only responsibility shall be to replace any quantity of the product proved defective. Seller and manufacturer shall not be liable for injury, loss or damage, direct or consequential, arising out of use or the inability to use the product. Nor shall seller or manufacturer be liable for any costs or expenses incurred in the processing or printing on the product. Before using, user shall determine the suitability of the product for its intended use. User assumes all risk and liability of every nature in connection therewith. No statements or recommendations other than those contained in the technical information published by Arlon shall have force or effect unless contained in an agreement manually signed by the officers of seller and manufacturer.

USA: 2811 S. Harbor Blvd. Santa Ana, CA 92704 – Telephone: 800-854-0361 – Fax: 714-540-7190

Customer Service: Telephone: 800-232-7161 – Fax: 800-329-2756 – Technical Services: 877-275-6698

EUROPE: North Sea Building, Gevers Deynootweg 93, 4th Floor, 2586BK Den Haag, The Netherlands – Telephone: +31 (0) 70 354-4311 – Fax: +31 (0) 70 355-7721

INDIA: 4F1 Court Chambers, 35 - New Marines Lines, Mumbai 400 020 – Telephone: +91 99 6755-3895

www.arlon.com