

DPF 210PB Polyester Roll-Up Banner

Digital Print Banner – Pebble Texture

DPF 210PB is a 9.8-mil (250 micron) premium, pebble textured, semi-rigid, coated polyester banner that is used in “roll-up or pop-up” banner applications. It has a gray, block-out layer that provides excellent opacity. DPF 210PB yields high print resolution and image quality, and has excellent lay-flat properties with minimal edgecurl. DPF 210PB is compatible with eco-solvent and solvent inks. Please use proper handling and correct profiles with appropriate heater settings for optimal prints*.

APPLICATIONS & FEATURES

- Digital printing with a wide variety of direct print systems.
- Indoor “roll-up” & “pop-up” display systems.
- Exhibitions, advertisements and point-of-purchase displays.

PERFORMANCE & PHYSICAL DATA

PROPERTY	TYPICAL VALUE	
WEIGHT	9.6 ± 0.25 oz	325 ± 20 g
THICKNESS	9.8-mil	250 micron
COLOR MAX DE	1.5 from Color Standard	
OPACITY / CONTRAST RATIO	95% + 5%	
GLOSS (GLOSS METER 60° REFLECTION)	0 - 15 unit	
TENSILE STRENGTH (WARP, WEFT)	Min. 100 lbs/in, 125 lbs/in	17.9 kg/cm, 22.3 kg/cm
ELONGATION (WARP, WEFT)	Min. 150%, 75%	
TEAR STRENGTH (WARP, WEFT)	Min. 35 lbs/in, 35 lbs/in	6.25 kg/cm, 6.25 kg/cm
PRINTING	Printable with Eco-Solvent and Solvent Inks	
SHELF LIFE	1 year from production date	
DURABILITY	Indoor, 1 year	

*Optimal print quality achieved by using Pre-heat settings between 38°C and 43°C, Platen/Print heat settings between 40°C and 45°C, Post/dryer setting at 55°C or maximum, recommended profiles and proper handling.

**Standard Terms & Conditions Apply

Effective Date 02.13

TERMS & CONDITIONS

The following is made in lieu of all warranties expressed or implied:

All statements, technical information and recommendations published by Arlon relating to Arlon products are based on tests believed to be reliable and within the accuracy of the equipment used to obtain the specific values. Their accuracy or completeness is not guaranteed and Arlon makes no warranty with regard thereto. Seller's and manufacturer's only responsibility shall be to replace any quantity of the product proved defective. Seller and manufacturer shall not be liable for injury, loss or damage, direct or consequential, arising out of use or the inability to use the product. Nor shall seller or manufacturer be liable for any costs or expenses incurred in the processing or printing on the product. Before using, user shall determine the suitability of the product for its intended use. User assumes all risk and liability of every nature in connection therewith. No statements or recommendations other than those contained in the technical information published by Arlon shall have force or effect unless contained in an agreement manually signed by the officers of seller and manufacturer.

USA: 2811 S. Harbor Blvd. Santa Ana, CA 92704 – Telephone: 800-854-0361 – Fax: 714-540-7190

Customer Service: Telephone: 800-232-7161 – Fax: 800-329-2756 – Technical Services: 877-275-6698

EUROPE: North Sea Building, Gevers Deynootweg 93, 4th Floor, 2586BK Den Haag, The Netherlands – Telephone: +31 (0) 70 354-4311 – Fax: +31 (0) 70 355-7721

INDIA: 4F1 Court Chambers, 35 - New Marines Lines, Mumbai 400 020 – Telephone: +91 99 6755-3895

www.arlon.com