

## **DPF 308 Banner**

## **Digital Print Mesh Banner**

DPF 308 is an 8-oz high quality, economical, white mesh banner with a PVC liner. The small-holed weave construction allows for both air-flow for wind resistance, as well as high resolution and high quality images. The blow through ratio is 15%. It is suitable to view graphics at a close distance. Furthermore, the banner features a fire resistant coating that passes the NFPA 701 fire resistant certification test. DPF 308 is rated for outdoor durability up to 1 year (unprinted). Printed durability is dependent on the ink system used.

#### **APPLICATIONS & FEATURES**

- Digital printing with a wide variety of direct print systems
- · Indoor merchandising and display graphics
- Film, TV, and Theater backdrops
- Outdoor advertising, i.e. building construction site advertising, building and scaffolding wraps, wallscapes
- Shorter-term banner applications

## **PERFORMANCE & PHYSICAL DATA**

| PROPERTY                  | TYPICAL VALUE  |
|---------------------------|--|
| THICKNESS                 | 0.014 in (0.355 mm)  |
| CONSTRUCTION              | 8 ox. flexible, mesh banner with PVC liner   |
| YARN (DENIER)             | 1000x1000 Denier   |
| THREAD COUNT              | 12 x 12  |
| TENSILE STRENGTH          | 200 / 185 lbf/in   |
| (WARP / WEFT)             |  |
| TEAR STRENGTH             | 40/30 lbf/in   |
| (WARP / WEFT)             |  |
| SERVICE TEMPERATURE RANGE | 14°F to 122°F (-10°C to 50°C)  |
| SHELF LIFE                | 1 year from factory shipment. (Free from excessive moisture, temperature, and direct sunlight. |
| FIRE RESISTANCE           | NFPA 701   |
| PRINTABILITY              | Standard UV solvent and eco-solvent digital inks   |

\*Standard Terms & Conditions Apply

Effective Date 03/12

# TERMS & CONDITIONS

The following is made in lieu of all warranties expressed or implied:

All statements, technical information and recommendations published by Arlon relating to Arlon products are based on tests believed to be reliable and within the accuracy of the equipment used to obtain the specific values. Their accuracy or completeness is not guaranteed and Arlon makes no warranty with regard thereto. Seller's and manufacturer's only responsibility shall be to replace any quantity of the product proved defective. Seller and manufacturer shall not be liable for injury, loss or damage, direct or consequential, arising out of use or the inability to use the product. Nor shall seller or manufacturer be liable for any costs or expenses incurred in the processing or printing on the product. Before using, user shall determine the suitability of the product for its intended use. User assumes all risk and liability of every nature in connection therewith. No statements or recommendations other than those contained in the technical information published by Arlon shall have force or effect unless contained in an agreement manually signed by the officers of seller and manufacturer.