

DPF 355

Digital Print Scrim PVC Banner

DPF 355 is a high quality, intermediate backlit 15-oz white, scrim PVC banner. This lightweight banner is ideal for any back illuminated indoor or outdoor signage. DPF 355 is digitally printable with a wide variety of printers using solvent, eco-solvent, and UV inks. The surface is smooth and yields high quality print resolution and image “pop.” The banner is both tear and curl resistant, and it is RF weldable. DPF 355 has been treated with UV inhibitors that aid in prolonging outdoor durability of up to 3 years (unprinted). Printed durability is dependent on the ink system used.

APPLICATIONS & FEATURES

- Digitally printable with a wide variety of direct print systems.
- Indoor & outdoor back illuminated signage.
- Shorter-term banner applications.

PERFORMANCE & PHYSICAL DATA

PROPERTY	TEST METHODS	TYPICAL VALUE
THICKNESS	Mil	14.90
	mm	0.378
CONSTRUCTION		15 oz. (510gsm) flexible, polyester scrim banner
YARN (DENIER)		500x500
THREAD COUNT		18x12
GLOSS (GLOSS METER 60° REFLECTION)		
MATTE	%	0-30
GLOSS	%	70-85
OPACITY	%	>75
TENSILE STRENGTH (ASTM)		
WARP (ALONG)	/lbs in	143.9
WEFT (ACROSS)	/lbs in	93.6
WARP (ALONG)	/kg cm	25.7
WEFT (ACROSS)	/kg cm	16.7
ELONGATION	%	21.2
TEAR STRENGTH (ASTM)		
WARP (ALONG)	/lbs in	31.6
WEFT (ACROSS)	/lbs in	37.5
WARP (ALONG)	/kg cm	5.64
WEFT (ACROSS)	/kg cm	6.70
SHELF LIFE		1 year from factory shipment. (Free from excessive moisture, temperature and direct sunlight)
PRINTABILITY		Standard solvent, eco-solvent and UV digital inks

*Standard Terms & Conditions Apply

Effective Date 06/12

USA: 2811 S. Harbor Blvd. Santa Ana, CA 92704 – Telephone: 800-854-0361 – Fax: 714-540-7190

Customer Service: Telephone: 800-232-7161 – Fax: 800-329-2756 – Technical Services: 877-275-6698

EUROPE: North Sea Building, Gevers Deynootweg 93, 4th Floor, 2586BK Den Haag, The Netherlands – Telephone: +31 (0) 70 354-4311 – Fax: +31 (0) 70 355-7721

INDIA: 4F1 Court Chambers, 35 - New Marines Lines, Mumbai 400 020 – Telephone: +91 99 6755-3895

www.arlon.com

TERMS & CONDITIONS

The following is made in lieu of all warranties expressed or implied:

All statements, technical information and recommendations published by Arlon relating to Arlon products are based on tests believed to be reliable and within the accuracy of the equipment used to obtain the specific values. Their accuracy or completeness is not guaranteed and Arlon makes no warranty with regard thereto. Seller's and manufacturer's only responsibility shall be to replace any quantity of the product proved defective. Seller and manufacturer shall not be liable for injury, loss or damage, direct or consequential, arising out of use or the inability to use the product. Nor shall seller or manufacturer be liable for any costs or expenses incurred in the processing or printing on the product. Before using, user shall determine the suitability of the product for its intended use. User assumes all risk and liability of every nature in connection therewith. No statements or recommendations other than those contained in the technical information published by Arlon shall have force or effect unless contained in an agreement manually signed by the officers of seller and manufacturer.

USA: 2811 S. Harbor Blvd. Santa Ana, CA 92704 – Telephone: 800-854-0361 – Fax: 714-540-7190

Customer Service: Telephone: 800-232-7161 – Fax: 800-329-2756 – Technical Services: 877-275-6698

EUROPE: North Sea Building, Gevers Deynootweg 93, 4th Floor, 2586BK Den Haag, The Netherlands – Telephone: +31 (0) 70 354-4311 – Fax: +31 (0) 70 355-7721

INDIA: 4F1 Court Chambers, 35 - New Marines Lines, Mumbai 400 020 – Telephone: +91 99 6755-3895

www.arlon.com